

INTRODUCTION

The **S-Control** is a mini single door control panel, can work with any Wiegand 26~37 bits output reader. It uses Atmel microcontroller to assure stable performance, and equips with an infrared remote control for easy operation. The **S-Control** supports 1,000 users, all user data can be transferred.

Features

- > 1,000 users, user data can be transferred
- > Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs
- > Can connect with any reader with Wiegand 26~37 bits output
- > Can connect with any keypad reader with 4bits, 8bits (ASCII), or 10bits Virtual number output
- > Support Master Card function
- > Low temperature resistance(-40°C)

Specifications

User Capacity	1,000
Operating Voltage Idle Current	9~24V DC <20mA
Relay Adjustable Relay Output Time Lock Output Load	One (NO, NC, Common) 1~99 Seconds (5 seconds default) 2 Amp Maximum
Wiegand Interface Input Output	Wiegand 26~37 bits Wiegand 26~37 bits (for user transfer)
Environment Operating Temperature Operating Humidity	Meets IP66 -40°C~60°C (-40°F~140°F) 0~90%RH
Physical Colour Dimensions Unit Weight Shipping Weight	ABS Shell Black (White optional) L65mm × W54mm × D19mm 40g 100g